



#### EX3-100-EARC Transmitter (Front)


#### EX3-100-EARC Receiver (Front)



### EX3-100-EARC Transmitter (Rear)



#### EX3-100-EARC Receiver (Rear)



# WyreStorm - Powerful. Reliable. Simple.

## Introduction

Extend 18Gbps A/V signals up to 100 meters over Cat6a with the EX3-100-EARC. This extender uses HDBaseT 3.0 technology, to send 4K HDR and Dolby Vision content at 60Hz. Compatible with eARC, you can transmit audio signals such as Dolby TrueHD/Atmos and DTS-HD MA 7.1 signals from a smart TV back to an eARC enabled AVR or soundbar. Flexible control passthrough options including IR, RS-232 and LAN allow you control a display and get devices connected over long distances.

# **Key Features**

- Uncompressed 18Gbps AV Signal Support: Experience top-notch video and audio quality with HDBaseT 3.0
- Backward Compatibility with ARC: Seamlessly integrate with existing ARC systems for hassle-free connectivity
- Bi-Directional IR and RS232 Transmission: Ensure reliable control and communication between your devices
- Optical Audio Return and Audio De-embed: Enjoy enhanced audio capabilities with optical audio return and the ability to separate audiofrom video signals
- Test Pattern Generation: Simplify troubleshooting with built-in test pattern generation

# In the Box

1x EX-100-USB3 1x DC 20V 3A Power Supply (US/EU/UK/AU) 1x 1.8m USB 3.0 Type-A to Type-B Cable (5Gbit/s) 4x Mounting Bracket with Screws 1x Quickstart Guide

# **Specifications**

Audio and Video			
	Transmitter	Receiver	
Inputs	1x HDMI: 19-pin Type A Female	1x HDBT: 8-pin RJ45 1x Optical In	
Outputs	1x HDBT: 8-pin RJ45 1x HDMI: 19-pin Type A Female 1x Optical Out	1x HDMI: 19-pin Type A Female	
	Cat 5e/6 (UTP): 40m/131ft - 4K@60Hz 4:4:4 24bpp Cat 6A (F/FTP or U/FTP) 100m/330ft - 4K@60Hz 4:4:4 24bpp		
Max. Video Resolution by Cable Type	<b>Note:</b> When the extender is set to Low-bandwidth mode (set the pin3 of the DIP switch on the transmitter to "Down" position):		
	Cat 5e/6 (UTP) 70m/230ft - 4K@60Hz 4:4:4 24bpp Cat 6A (F/FTP or U/FTP) 100m/330ft - 4K@60Hz 4:4:4 24bpp		
Output Video Encoding	Format: HDBaseT Encoding Data Rate: 18Gbps End to End Latency: 10µs (microseconds)		
Audio Formats	HDMI: HDMI 2.0 formats including multi-channel PCM, Dolby True-HD and DTS-HD master audio   ARC Mode: 5.1-ch compressed audio (such as Dolby Digital, DTS 5.1, and Dolby Digital Plus), and 2.0-ch uncompressed PCM audio   eARC Mode: Up to 8-ch L-PCM of 24 bit, 192kHz audio. Supports encoded audio formats, such as Dolby Atmos and DTS-X   OPTICAL Audio Return Mode: 5.1-ch compressed audio, such as Dolby Digital, DTS 5.1, and Dolby Digital Plus, and 2.0-ch uncompressed PCM audio   OPTICAL De-embed Mode: 2.0-ch uncompressed PCM audio   AUDIO OUT: PCM 2.0		
HDR Support	HDR 10, HDR 10+, HLG, and Dolby Vision (low-latency mode)		
Supported Standards	DCI   RGB   HDR10   Dolby Vision   HLG   BT.2020   BT.2100		
Maximum Pixel Clock	600Mhz		
Communication and Control	, ,		
HDMI	HDMI   HDCP 2.3   EDID   CEC Pass-through		
HDBaseT	HDMI   HDCP 2.3   EDID   RS-232 Pass-through   IR Pass-Through  2- WAY PoH   CEC Pass-through		
IR	1x IR RX: 3.5mm (1/8in) TRS Stereo   1x IR TX: 3.5mm (1/8in) TS Mono (Transmitter and Receiver)		
RS-232	1x RS-232: 3-pin Phoenix (Transmitter and Receiver)		
Ethernet	Ethernet Pass-through of up to 1Gb		
Power			
Power Supply	12V DC 2A (Sold separately)	12V DC 2A (Sold separately)	
Power Consumption	20.04W		
Environmental			
Operating Temperature	0 to + 45°C (32 to + 113 °F), 10% to 90%, non-condensin	0 to + 45°C (32 to + 113 °F), 10% to 90%, non-condensing	
Storage Temperature	-20 to +70°C (-4 to + 158 °F), 10% to 90%, non-condensir	Ig	
Dimensions			
Length x Width x Height	300mm x 180mm x 25mm		
Weight	0.59Kg/1.30lbs		
Regulatory			
Safety and Emission	CE   FCC   RoHS   RCM   EAC   UKCA		
	1		

Note: WyreStorm reserves the right to change product specification, appearance or dimensions of this product at any time without prior notice.

#### Warranty Information

WyreStorm Technologies ProAV Corporation warrants that its products to be free from defects in material and workmanship under normal use for a period of five (5) years from the date of purchase. Refer to the Product Warranty page on wyrestorm.com for more details on our limited product warranty.

