




The NovoDisplay DK series is an Ultra HD 4K professional display for signage applications in landscape or portrait mode.

With built-in NovoDS it is easy to create, publish and manage promotional announcements and company messages.

For meetings, the display can easily be switched to 'presentation' mode featuring NovoConnect wireless collaboration.

This series is available in various display sizes, suitable for commercial applications such as hospitality, retail, education and business.





## Key Features



### Digital Signage

The built-in digital signage solution is easy to set up and manage via the optional NovoDS Cloud service or included NovoDS Studio software.

The user can toggle between the Wireless Collaboration and Digital Signage function to maximise the use of the display at any time.



### 4K-UHD Resolution

The DK series is available in 43"/55"/65"/75"/86" display size with 4K Ultra-HD (3,840 x 2,160) resolution to deliver outstanding details and stunning visuals.

The unparalleled display with 500 nits brightness and 50,000 hours performance make this a truly professional signage display for many applications.





### Support Landscape & Portrait Installation

The DK series easy to install and can support landscape and portrait mode to cater for various business needs.



### Bulletin board


The Bulletin board is a template in the optional NovoDS Cloud that allows for easy creation of a pin board layout and added interactivity with documents.

Ideally suited to replace the traditional paper pin boards with up to date information that is easily maintained.



### Backlit D-LED Technology

Backlit D-LED (IPS panel) technology offers brighter pictures, flawless colors, richer textures, and extra wide viewing angles (178°/ 178°) with an incredibly sharp and crisp images.



### NovoConnect Wireless Collaboration

The DK series has built-in NovoConnect for cable-free and hassle-free presentations and collaboration in the classroom or in office.

NovoDisplay is ready for hybrid meetings with video conferencing.



## Product Specifications

| Brand/ Model Name        |   | DK433   | DK553                | DK653                  | DK753               | DK863                  |
|--------------------------|---|---|----------------------|------------------------|---------------------|------------------------|
| Display                  | Panel Size  | 43"   | 55"                  | 65"                    | 75"                 | 86"                    |
|                          | Type/Technology                                   | Backlit D-LED   |                      |                        |                     |                        |
|                          | Brightness (Typ)                                  | 500 cd/m2   |                      |                        |                     |                        |
|                          | Native Resolution                                 | 4K Ultra-HD (3840 x 2160)   |                      |                        |                     |                        |
|                          | Viewing Angle (H/V)                               | 178° / 178°   |                      |                        |                     |                        |
|                          | Aspect Ratio                                      | 16:9  |                      |                        |                     |                        |
|                          | Response Time (MS)                                | 8 ms  |                      |                        |                     |                        |
|                          | Estimated Life Time (Typ.)                        | 50, 000 Hours   |                      |                        |                     |                        |
|                          | Display Color (Bit)                               | 1.07 billion (10-bit)   |                      |                        |                     |                        |
|                          | Installation Orientation                          | Portrait & Landscape  |                      |                        |                     |                        |
|                          | Daily Operation (Hours/Days)                      | 24/7  |                      |                        |                     |                        |
|                          | Bezel Size  | 43"- 7.9mm/ 55"- 9.9mm/ 65"- 14.8mm/ 75"- 15.3mm/ 86"- 18mm   |                      |                        |                     |                        |
| Touch                    | Input   | HDMI v2.0(ARC, HDCP v2.2) x2, Audio-In (3.5mm) x1 RS-232 (RJ45) x1  |                      |                        |                     |                        |
|                          | Output  | HDMI-Out x1 4K@60Hz (Optional), USB-A x2 (Support up to 32GB), microSD Slot x1 (Support up to 32GB), Audio-Out (3.5mm) x1, RS-232 x1, RJ45 x1   |                      |                        |                     |                        |
|                          | WiFi  | 802.11ac x1   |                      |                        |                     |                        |
|                          | IR Receiver (Front)                               | x1 (±25° Angle, >8m Distance)   |                      |                        |                     |                        |
|                          | System  | OS Version  | Android™ v9.0        |                        |                     |                        |
| Internal Storage         |   | 32GB (eMMC Flash) Standard  |                      |                        |                     |                        |
| Digital Signage          | Supported Widget                                  | Announcement Mode, Agenda, Social Networks, Weather, Calendar, Clocks, HTML 5 Rendering, Remote Media, People Counting (camera not included)  |                      |                        |                     |                        |
|                          | Video decoding                                    | Single 4K@60fps   |                      |                        |                     |                        |
| Wireless Collaboration   | BYOD Supported System                             | Windows 7 / 8 / 10 (32 bits and 64 bits), macOS 10.7 and above, Ubuntu, iOS 7.0 (Airplay) and above, Android 4.0 (Google Cast) and above, Chromebook  |                      |                        |                     |                        |
|                          | Simultaneous Connections Simultaneous On-screen / | NovoConnect Lite - 8 connections / 1, 2 split screen  |                      |                        |                     |                        |
| Speaker                  | Internal  | 10 x2 (Stereo)  |                      |                        |                     |                        |
| Power                    | Power Supply (Internal)                           | AC 100-240V, 50/60Hz  |                      |                        |                     |                        |
|                          | Consumption (without OPS)                         | ≤198W   | ≤198W                | ≤220W                  | ≤330W               | ≤410W                  |
|                          | Standby Mode                                      | <0.5W (Standby)   |                      |                        |                     |                        |
| Physical Characteristics | Dimension (L x H x D)mm                           | 961.6 x 567.3 x 72.8  | 1,243.2 x 714 x 69.6 | 11461.4 x 846.9 x 80.4 | 1682 x 962.2 x 76.3 | 1,714.2 x 992.4 x 97.2 |
|                          | Weight Kg   | 8.9kg   | 14.2kg               | 22.8kg                 | 31.2kg              | 42.8kg                 |
|                          | VESA Mounting (FPMPMI)                            | 4 - M6, 400 x 200mm   |                      |                        | 4 - M8, 600 x 400mm |                        |
|                          | Frame Color                                       | Black   |                      |                        |                     |                        |
| Accessories              | Standard  | AC Power Cord, Remote Control, Documentation Kit  |                      |                        |                     |                        |
|                          | Optional  | NovoDS Cloud (incl Bulletin Board), OPS module (80 pin) – including NovoConnect full version, NT Live and BYOM – LauncherPlus(WQL-400), LauncherOne, VIVOTEK SC81831 camera, Wall Mount Kit |                      |                        |                     |                        |
| Warranty                 | Standard  | 3 years warranty  |                      |                        |                     |                        |

[www.vivitek.eu](http://www.vivitek.eu) | [www.novoconnect.eu](http://www.novoconnect.eu)

©2022 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.

Reference number: 09/2022

A brand of 