

KA11 11 inch Countertop/Wall Touchpanel

The KA11 touch panel is the ultimate choice for simple, intuitive control of the entertainment, environment and security systems in residential or commercial facilities. It features a fully customizable 11.6" widescreen LCD display with 1920x1080 FHD resolution and integrated capacitive touchscreen. The sleek touchpanel is easily wall mounted or an accessory stand is available for table top installations. The ambient light and proximity sensors automatically adjust the screen brightness and LED backlight according to the environmental light level*. Built-in gigabit Ethernet with PoE and 802.11 b/g/n dual band WiFi, enable video from IP security cameras, video intercom functionality*, enhanced two-way feedback and remote programming updates.

Key Features

- 11.6" widescreen LCD with 1920x1080 Full HD resolution and integrated capacitive touchscreen, supporting multi-touch and gesture.
- Fully customizable interface can be programmed in portrait or landscape mode.
- Innovative design allows wall mount in dual gang electrical box or table top installation using stand accessory (sold separately).
- Ambient light and proximity sensor adjusts the screen brightness and LED backlights automatically according to the environmental light level.*
- Powered by a separate power supply or PoE.
- Gigabit Ethernet with PoE and 802.11 b/g/n dual band WiFi enable video from IP security cameras, enhanced two-way feedback and remote programming updates.
- Video intercom capability with built in camera, microphone and speakers (future use)*.

* Intercom functionality and support for proximity and ambient light sensor will be enabled with a future firmware update



Installation Options



Countertop Installation with Table Stand



On-Wall Installation with Two-Gang Electrical Box

Specifications

Power (Power Supply not included).....+24V DC, 1A or PoE
 Power Management.....Adjustable backlight/ proximity sensor
 Touchscreen Display..... High-brightness color IPS LCD
 Full HD (1920x1080 pixels) with 16.7M colors
Integrated high-resolution projected capacitive touchscreen
 Display Size..... 11.6in (294mm) diagonal
 Display Backlight..... LED Backlit, 350nit
 Ethernet Port..... RJ-45, 10/100/1000 Base-T with Power-over-Ethernet
 Wireless Ethernet..... 2.4GHz & 5.0GHz, 802.11 b/g/n
 Camera.....Color CMOS, 8MP, 30FPS
 Microphone.....Built-in Microphone, Echo cancellation and noise suppression,
 Voice activity detection
 Speakers..... Two (2), Stereo 2 Watt
 Communications.....USB programming port
 Total System Memory..... 2GB DDR3, 8GB eMMC Flash
 Device Capability..... Total number of devices is limited only by memory
 Macro Capability..... Total number of macros is limited only by memory
 Operating Temperature..... +32°F to +122°F (0°C to +50°C)
 Operating Humidity..... 5% to 95% Non-condensing
 Mounting..... Tabletop with Aluminum Stand or Wall-Mount
 Installation..... US standard 2 gang low voltage bracket (included)
 Outer Bezel Dimension (W x H)..... 12.4in (313mm) x 7.9in (201mm)
 Depth in Wall..... 0.83in (21mm)
 Warranty..... Three Years (Parts & Labor)
 All Specifications subject to change without notice.



RTI User Interfaces

Remote Controls
 Keypads
 Audio Control Keypads
 In-Wall Touchpanels
 Tabletop Touchpanels
 Mobile Apps



RTI Control Accessories

Control Processors
 System Kits
 RS-232 Modules
 IR Modules
 Relay Modules
 Z-Wave Modules



RTI Audio/Video Distribution

HDMI Splitters & Switchers
 HDMI Matrix Switchers
 HDBaseT Matrix Switchers
 HDBaseT Extenders
 Presentation Switchers
 Video over IP Transceivers



Remote Technologies Incorporated
 5775 12th Avenue East, Suite 180, Shakopee, MN 55379
 PH: (952) 253-3100 • Website: www.rticorp.com

RTI
 It's Under Control®