

ViewSonic® LCD DISPLAY **XG2705-2**

Key Features

- 27-inch 3-side Borderless Display
- 144Hz Refresh Rate
- 1ms (GtG) Response Time
- AMD FreeSync™ Premium



Product Description

The XG2705-2 27" IPS 144Hz gaming monitor is designed for hardcore and casual gamers alike, providing the perfect blend of hyper-responsive control and vivid IPS color. A sleek 3-side borderless, esports-inspired design and 1ms (GtG) response time with AMD FreeSync™ Premium, outputs fluid, seamless visuals for every gaming scenario.

Visit Us  www.viewsonic.com

DISPLAY

Display Size (in.):	27
Viewable Area (in.):	27
Panel Type:	IPS Technology
Resolution:	1920 x 1080
Resolution Type:	FHD
Static Contrast Ratio:	1,000:1 (typ)
Dynamic Contrast Ratio:	80M:1
Light Source:	LED
Brightness:	250 cd/m ² (typ)
Colors:	16.7M
Color Space Support:	8 bit (6 bit + FRC)
Aspect Ratio:	16:9
Response Time (Typical GTG):	1ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	144
Adaptive Sync:	FreeSync
Blue Light Filter:	Yes
Flicker-Free:	Yes
Color Gamut:	NTSC: 72% size (Typ) sRGB: 104% size (Typ)
Pixel Size:	0.311 mm (H) x 0.311 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

COMPATIBILITY

PC Resolution (max):	1920x1080
Mac® Resolution (max):	1920x1080
PC Operating System:	Windows 10 certified; macOS tested
Mac® Resolution (min):	1920x1080

CONNECTOR

3.5mm Audio Out:	1
HDMI 1.4:	2
DisplayPort:	1
Power in:	3-pin Socket (IEC C14 / CEE22)

AUDIO

Internal Speakers:	2Watts x2
--------------------	-----------

POWER

Eco Mode (Conserve):	19W
Eco Mode (optimized):	23W
Consumption (typical):	26W
Consumption (max):	34W
Voltage:	AC 100-240V, 50/60 Hz
Stand-by:	0.5W
Power Supply:	Internal

ADDITIONAL HARDWARE

Kensington Lock Slot:	1
Cable Organization:	Yes

CONTROLS

Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	100 x 100 mm
------------------	--------------

INPUT SIGNAL

Frequency Horizontal:	HDMI (v1.4): 30 ~ 180KHz, DisplayPort (v1.2): 180 ~ 180KHz
Frequency Vertical:	HDMI (v1.4): 48 ~ 144Hz, DisplayPort (v1.2): 48 ~ 144Hz

VIDEO INPUT

Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2)
---------------	--

ERGONOMICS

Height Adjust (mm):	120
Swivel:	90°
Tilt (Forward/Back):	-5° / 15°
Pivot (Right/Left):	90° / 0°

WEIGHT (IMPERIAL)

Net (lbs):	15.7
Net Without Stand (lbs):	8.5
Gross (lbs):	20.5

WEIGHT (METRIC)

Net (kg):	7.1
Net Without Stand (kg):	3.9
Gross (kg):	9.3

DIMENSIONS (IMPERIAL) (WXHxD)

Packaging (in.):	29.1 x 17.6 x 7.5
Physical (in.):	24.1 x 17.08~21.32 x 9.4
Physical Without Stand (in.):	24.1 x 14.5 x 1.9

DIMENSIONS (METRIC) (WXHxD)

Packaging (mm):	738 x 448 x 191
Physical (mm):	612 x 433.9~541.5 x 239
Physical Without Stand (mm):	612 x 367 x 47

GENERAL

Regulations:	cTUVus, FCC-B, ICES003, CEC, S-mark, MX-CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BSMI, RCM, GEMS, VCCI, PSE, KC, e-Standby, CCC, China RoHS, China Energy Label
--------------	---

PACKAGE CONTENTS:	XG2705-2 x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male-Male) x1, Quick Start Guide x1
-------------------	---

Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
-------------------	--

Warranty:	*Warranty offered may differ from market to market
-----------	--